

⇒ SF 2 AND OPTIONAL TRIMMER

WIRE-STITCH BOOKLETMAKER

wire-fed stitching system provides lower operating costs than bookletmakers using pre-formed staples | produces booklets up to 100 pages* | low maintenance—jogs, stitches, and folds up to 65,000 booklets without replacing wire spools | runs on-line with a variety of collators (interface is included) including the MBM FC 10 | easy to use, push-button controls with 6 digit counter | staple leg adjustment feature allows staple length to be custom fit to the size of book being run | heavy-duty clutch and bearings | moveable, magnetic stitching heads | one-step threading for quick and easy set-up | knife fold with dual fold rollers for crisp, consistent folds | powered exit conveyor | transparent safety access covers—machine will not operate with covers in open position | includes back jog, and stand with casters | optional activated clinch, and on-line corner/side stitch gate

Dimensions (D x W x H): 21 x 52 x 24 ½ inches, Shipping weight: 400 lbs.

OPTIONAL FACE TRIMMER FOR SF 2 BOOKLETMAKER

operates on-line with SF 2 bookletmaker | trims booklets up to 100 pages* | powered exit conveyor | transparent safety access cover—machine will not operate with cover in open position

Dimensions (D x W x H): 24 ¼ x 48 ½ x 24 inches, Shipping weight: 402 lbs.




ONE-STEP THREADING



Magnetic stitching heads feature one-step threading for quick and easy set-up.

POWERED CONVEYOR



The powered exit conveyor on the bookletmaker or trimmer stacks booklets neatly.

⇒ SF 2

Speed	2,300 sets/hr*
Sheet capacity	25*
Paper size	4 ¾" x 8 ½" to 12 ¾" x 18 ½"
Power supply	115 V, 60 Hz

⇒ OPTIONAL TRIMMER

Speed	2,300 sets/hr*
Sheet capacity	25*
Paper size	4 ¾" x 8 ¾" to 12 ¼" x 18 ¼"
Power supply	115 V, 60 Hz

* may vary due to variations in paper and power supply

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com

WWW.WHITAKERBROTHERS.COM
3 TAFT COURT
ROCKVILLE, MD 20850
800-243-9226

All technical data is approximate and subject to change. © MBM Corporation 2/2017

OPTIONAL TRIMMER



TRIMMER FEATURES:

- In-line face trimming of booklets
- Jam detection
- Electrical interface for communication with StitchFold Bookletmaking System
- Safety interlock
- See-through top cover

TRIMMER SPECIFICATIONS:

Unit Weight: 236 Pounds

Speed: Up to 2,400 booklets per hour (115 Vac machine)

Capacity: Minimum: 4.00" cut width x 4.13" to fold (trim length)

2 sheets 20# bond thickness

Maximum: 12.71" cut width x 9.00" to fold (trim length)

50 sheets 20# bond thickness (0.20")

.625" maximum material trim

Booklets: 4.25" x 5.5", 5.5" x 8.5", 8.5" x 11", 4.75" x 4.75 "CD", & metric sizes*

Output: Indexing conveyor

Footprint: 16.50" x 18.38"

Dimensions: Height 27.38" Width 26.42" (Length without discharge table 25.90")

Length with fully extended discharge table 48.44"

Modes: Trim or No-trim

Electrical: Standard outlet - 115 Volts, 60 Hz, 6 Amps (1/4 HP)

Optional: 230 Vac, 50 Hz, 3 Amps

*All booklets with or without trim stock on one or three sides

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com